

## MUFLE 4ALL H92 combined with


## Galvanized steel 4Stone grating


Black: 613057

613059

**Grey:** 

| <b>_</b> | 1000  |   |     |   |       |       |       |       |   |       |     |   |     |     |   |       |      |       |       |       |       |       |       |     |     |       |       |       |       |       |       |       |       |       |       |       |     |       |     |       |       |       |       |       |       |       |       |       |
|----------|-------|---|-----|---|-------|-------|-------|-------|---|-------|-----|---|-----|-----|---|-------|------|-------|-------|-------|-------|-------|-------|-----|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|          |       |   |     |   |       |       |       |       |   |       |     |   |     |     |   |       |      |       |       |       |       |       |       |     |     |       |       |       |       |       |       |       |       |       |       |       |     |       |     |       |       |       |       |       |       |       |       |       |
|          |       |   |     |   | _     | _     |       |       |   |       | _   |   |     |     |   |       |      |       |       |       |       |       |       |     |     |       |       |       |       |       |       |       |       |       |       |       |     |       |     |       |       |       | _     |       |       |       |       |       |
| "        | 000   | Ö | ŏ   | _ | 000   | 0 0 0 | 0 0 0 | Õ     | ō | ŏ     | 0   | 0 |     | ) ( | Ö | Ö     | 0000 | 0000  | 000   | 000   | 000   | 0 0 0 | 000   | 000 | 000 | 0 0 0 | 000   | 000   | 0 0 0 | 0 0 0 | 000   | 0 0 0 | 0 0 0 | 000   | 000   | 0000  | 000 | 0 0 0 | 000 | 000   | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 000   | 000   |       |
| 0        | 0 0 0 |   | 0 0 | 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 | 0 0 0 | 0 0 | 0 | ) ( | ) ( | 0 | 0 0 0 | 000  | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 000 | 000 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 000 | 0 0 0 | 000 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 |
| Ę        |       |   |     |   | F     | 3     |       |       |   |       |     |   |     |     |   |       |      |       | Θ.    |       |       |       |       |     |     |       |       |       |       | -     |       |       |       |       |       | _     |     |       |     |       |       |       |       |       |       |       |       |       |





## **Dimensions and features**

| Length (mm)                   | 1000                       |
|-------------------------------|----------------------------|
| Width External/Internal (mm)  | 120 / 95                   |
| Height External/Internal (mm) | 132 / 70                   |
| Outlets                       | Vertical outlet Ø110 / Ø75 |
| Channel body material         | PP-PE                      |
| Frame                         | integrated                 |
| Grating material              | Galvanized steel           |
| Grating slot dimension (mm)   |                            |
| Grating surface finishing     | Galvanized                 |
| Weight (Kg)                   | 2,8                        |
| Resistance (Norm EN1433)      | Pedestrian Application     |

Dimensions and weights are subjected to the tolerances of the manufacturing. The products have to be installed according to ACO's installation manual.